



 ΔT

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE FOR STONEX HOMES

BUILDING CONSENT

PROJECT ISSUE: 23/11/09



Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55 www.siliconarchitecture.com



| Check 140. | Sheet Name | 1101.110. | I tov. Date |
|------------|--|-----------|-------------|
| | | | |
| A000 | COVER PAGE | | |
| A001 | SHEET LIST | | |
| A004 | CONSTRUCTION NOTES | | |
| A100 | EXISTING SITE PLAN | | |
| A101 | PROPOSED SITE PLAN | 1 | 25/01/2024 |
| A102 | OUTLOOK/OUTDOOR/TRACKING CURVES | 2 | 22/02/2024 |
| A103 | PROPOSED SITE DRAINAGE PLAN | 1 | 25/01/2024 |
| A104 | PROPOSED SITE SEDIMENT PLAN | 1 | 25/01/2024 |
| A105 | PROPOSED SITE PLAN - SLAB SETOUT | | |
| A201 | GROUND FLOOR PLAN | 3 | 28/02/2024 |
| A202 | PROPOSED ROOF PLAN | | |
| A203 | PROPOSED PLUMBING LAYOUT | | |
| A204 | WALL SETOUT PLAN | 3 | 28/02/2024 |
| A205 | WALL REFERENCE PLAN | | |
| A301 | PROPOSED ELEVATIONS | 1 | 25/01/2024 |
| A302 | PROPOSED ELEVATIONS | 1 | 25/01/2024 |
| A305 | DOORS & WINDOWS SCHEDULE | 1 | 25/01/2024 |
| A306 | DOORS & WINDOWS SCHEDULE | 1 | 25/01/2024 |
| A401 | PROPOSED SECTIONS | 1 | 25/01/2024 |
| A402 | PROPOSED SECTIONS | 1 | 25/01/2024 |
| A501 | DETAIL - ROOF JUNCTIONS | | |
| A502 | DETAIL - ROOF JUNCTIONS | | |
| A503 | DETAIL - ROOF JUNCTIONS/ISOMETRICS | | |
| A504 | DETAIL - ROOF ISOMETRICS | | |
| A505 | DETAIL - EXTERNAL WALL CORNER | | |
| A506 | DETAIL - WALL BASE JUNCTIONS | | |
| A507 | DETAIL - WINDOW JOINERY | | |
| A508 | DETAIL - GARAGE JOINERY / WALL PENETRATION | | |
| A509 | DETAIL - WALL PENETRATIONS | | |
| A510 | DETAIL - OPENINGS | | |
| A511 | DETAIL - LUMBERLOK | | |
| A512 | DETAIL - GIB WET AREAS | | |
| A513 | DETAIL - GIB WET AREAS | | |


AΤ

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE for STONEX HOMES

Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55

www.siliconarchitecture.com





AΤ

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE for STONEX HOMES



Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55 www.siliconarchitecture.com





AΤ

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE for STONEX HOMES



Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55 www.siliconarchitecture.com

- 3. ALL PARTITIONS SHALL BE PERPENDICULAR OR PARALLEL TO BUILDING CORE WALLS, UNLESS OTHERWISE NOTED.
- 4. HINGE FACE OF ALL DOOR OPENINGS SHALL BE LOCATED 100MM FROM ADJACENT PERPENDICULAR WALL, UNLESS OTHERWISE NOTED.
- 5. WHERE EXISTING ACCESS PANELS CONFLICT WITH CONSTRUCTION, RELOCATE PANELS TO ALIGN WITH AND FIT WITHIN NEW CONSTRUCTION. (REVIEW WITH DESIGN CONSULTANT IN THE FIELD)
- 6. REPAIR AND/OR RESTORE ALL EXISTING FIREPROOFING DAMAGED DUE TO DEMOLITION. FIREPROOFING SHALL BE AS REQUIRED TO MAINTAIN EXISTING FIRE PROTECTION RATING.
- 7. PATCH AND REPAIR ALL EXISTING AND/OR NEW PENETRATIONS THROUGH EXISTING FIRE RATED SLABS
- PARTITIONS. AS REQUIRED. TO MAINTAIN EXISTING FIRE PROTECTION RATING.
- 8. PATCH AND REPAIR ALL EXISTING WALLS, COLUMNS AND SURFACES SCHEDULED TO REMAIN AS REQUIRED TO LEAVE THEM SMOOTH AND EVEN TO RECEIVE NEW SCHEDULED FINISHES. REFER TO FINISH PLAN FOR ADDITIONAL INFORMATION.
- 9. VERIFY ALL MEASUREMENTS AND DIMENSIONS ON SITE PRIOR TO FABRICATION AND CONSTRUCTION. DO NOT SCALE MEASUREMENTS FROM THESE DRAWINGS.
- 10. MARK AND SET OUT ALL PARTITIONS AND JOINERY LOCATIONS PRIOR TO CONSTRUCTION/INSTALLATION, FOR PROJECT MANAGER APPROVAL
- 11. CONSTRUCTION TO COMMENCE ONLY ONCE APPROVAL HAS BEEN GRANTED IN WRITING BY PROJECT MANAGER.
- 12. ALL NEW PARTITIONS TO COMPLY WITH ALL RELEVANT BCA REQUIREMENTS, NEW ZEALAND STANDARDS AND MANUFACTURERS INSTRUCTIONS.
- 13. THE GLAZING DETAILS SHOWN ON THESE ARCHITECTURAL DRAWINGS ARE INDICATIVE ONLY OF THE DESIGN INTENT. THE GLAZING SUB-CONTRACTOR IS RESPONSIBLE FOR THE CORRECT DETERMINATION OF GLASS THICKNESS, WIND AND SEISMIC LOADING.
- 14. THE SLIP RESISTANCE OF ALL FLOOR FINISHES INCLUDING STAIR FINISHES SHALL COMPLY WITH THE REQUIREMENTS OF THE BCA, AS/NZS 4586 AND HB
- 15. HEAD CONTRACTOR IS TO ALLOW FOR AND PROVIDE ALL MATERIALS, LABOUR AND ACCESSORIES NECESSARY TO COMPLETE THE WORKS TO THE SPECIFIED PERFORMANCE. NO VARIATIONS WILL BE CONSIDERED FOR THE PROJECT UNLESS IT IS A CLEAR CHANGE TO THE INTENT AND SCOPE OF THE WORKS INITIATED IN WRITING BY THE PROJECT MANAGER.
- 16. CONTRACTOR TO ENSURE ADEQUATE STRENGTH AND STABILITY OF ALL ITEMS FOR THEIR INTENDED USE AND IN ACCORDANCE WITH THE BCA STANDARDS.
- REFER TO STRUCTURAL ENGINEER'S DRAWINGS

FOR STRUCTURAL DETAILS AND CALCULATIONS. REFER TO STRUCTURAL ENGINEER'S DRAWINGS FOR FOUNDATION LAYOUT, LINTEL AND STEEL BEAMS SIZES AND DETAILS.

ARCHITECTURAL DRAWINGS ARE TO BE READ IN CONJUNCTION WITH STRUCTURAL DRAWINGS.

PRIOR TO COMMENCING ANY WORK ON SITE. DO NOT SCALE OFF DRAWINGS, CONTACT ARCHITECT FOR ANY DISCREPANCIES.

SITE MANAGEMENT 1) PLAN EXCAVATION TO MINIMISE EXPOSURE

2) REMOVE EXCAVATED SOIL TO AN APPROVED

3) PROTECT THE CUT FACE TO MINIMISE RUNOFF FROM SITES ABOVE.

4) INSTALL DRAIN COIL IN FILTER SOCK BEHIND RETAINING WALL FALLING TO CESSPIT AND INTO S.W. DRAINAGE SYSTEM.

5) PROVIDE SILT FENCE CLEAR OF BUILDING **WORKS AS NECESSARY.**

6) AT FUTURE DRIVE (SITE ACCESS) LAY METAL AS CLEANING AREA.

7) MAINTAIN AND CLEAN OUT SILT RETENTION DEVICES AS NECESSARY.

8) RETAIN VEGETATION BUFFER STRIPS AT STREET AND FORM CONTOUR DRAINS AS NECESSARY TO SLOW THE SPEED OF RUNOFF TO MINIMISE SLIT RUNOFF TO STREET.

9) PLACE 50mm GAP7 METAL OVER WHOLE OF CUT AREA TO REDUCE DRYING AND MINIMISE SILT RUNOFF. NOTE:

ALL CESSPITS: BEST POSITION TO BE DETERMINED AND CONFIRMED ON SITE BY THE SITE SUPERVISOR.

SITE AND SERVICES NOTE:

EROSION & SEDIMENT CONTROL: 1) EXCAVATE SITE AS REQUIRED & PROTECT ANY CUT FACES TO MINIMISE RUNOFF FROM SITES ABOVE

2) ERECT SIT FENCE AS REQUIRED. PROVIDE HARDSTAND AT PROPOSED DRIVEWAY AREA FOR CONSTRUCTION VEHICLES & CLEANING. RETAIN VEGETATION BUFFER STRIP AT STREET & FORM CONTOUR DRAINS AS REQUIRED TO REDUCE THE SPEED & AMOUNT OF RUNOFF TO THE STREET.

PUBLIC DRAINS: CONTRACTOR SHALL LOCATE DRAIN/S PRIOR COMMENCEMENT OF ANY RELEVANT FOUNDATION AT WORK.

ELECTRIC & GAS: ALL ELECTRIC & GAS SERVICES SHALL BE INSTALLED & LOCATED AS PER THEIR APPROPRIATE, STANDARDS & REGULATIONS.

WHERE APPROPRIATE, KEYSTONE RETAINING WALLS CAN BE USED INSTEAD OF TIMBER, PROVIDING THEY ARE DESIGNED & INSTALLED TO THE CORRECT SURCHARGES (PS1 MAY BE REQUIRED)

CONFIRMED ON SITE BY THE SITE SUPERVISOR.

SITE FENCE SAFETY

FENCES SHALL EXTEND AT LEAST 2.0M IN HEIGHT FROM GROUND LEVEL ON THE SIDE ACCESSIBLE TO THE PUBLIC. AN ACCEPTABLE FENCE MAY BE CONSTRUCTED WITH GALVANISED CHAINLINK NETTING HAVING A MAXIMUM SIZED GRID OF 50 MM X 50 MM. POST

TIMBER FRAMING NOTES: CONSTRUCTION NOTES 35 Building Consent BCO10375996 Approved by Auckland Council Roof CLADDING 90 X 45 TOP PLATES WITH AN ADDITIONAL 140 X 35 TRS5 - 0.40BMT METAL LONG RUN ROOFING - INSTALL

PLATE. 90 X 45 BOTTOM PLATE 90 X 45 NOGS

TOP PLATE TO STUD FIXING: LUMBERLOK STUD TO TOP PLATE FIXING TYPE "B". REFER TO LUMBERLOK SPEC FOR FIXING DETAILS AND REQUIREMENTS

BOTTOM PLATE FIXING TYPICAL: (ON CONCRETE FLOOR)

PROPRIETARY POST FIXED ANCHORS WITHIN 150MM OF EACH END OF THE PLATE & BE SPACED AT A MAX. OF 900MM ¢, OR 600MM ¢ WHEN USED ON SLAB EDGES FORMED BY MASONRY HEADER BLOCKS

FOR EXTERNAL WALL PROPRIETARY ANCHORS SHALL HAVE A MINIMUM CAPACITY WHEN TESTED IN ACCORDANCE WITH 2.4.7 OF NZS 3604:2011 AS FOLLOWS:

(A) HORIZONTAL LOADS IN THE PLANE OF THE WALL - 2KN; (B) HORIZONTAL LOADS OUT OF PLANE OF THE WALL - 3KN; (C) VERTICAL LOADS IN AXIAL TENSION OF THE FASTENER - 7KN.

FOR INTERNAL WALLS: PROPRIETARY ANCHORS SHALL A MINIMUM CAPACITY WHEN TESTED IN ACCORDANCE WITH 2.4.7 OF NZS 3064:2011 AS FOLLOWS: (A) IN THE PLANE OF THE WALL - 2KN; (B) OUT OF PLANE OF THE WALL - 2KN

BOTTOM PLATE FIXING: (ON TIMBER FLOOR) EXTERIOR & LOAD BEARING FRAMING SHALL HAVE: TIMBER BOTTOM PLATES TO TIMBER FLOORS SHALL BE FIXED TO FLOOR FRAMING AT: A) EXTERNAL WALLS & INTERNAL WALL BRACING **ELEMENTS** 3/90 X 3.15 Ø NAILS @ 600¢ B) INTERNAL WALLS - 90 X 3.15Ø NAILS @600¢

TREATMENT REQUIREMENTS FOR FRAMING TIMBER AND WOOD BASED PRODUCTS (As per NZS 3602:2003)

FLOORING UNDER WET AREA H3.2 STRANDFLOOR H3.2

ENCLOSED FLAT ROOF MEMBERS H1.2 KD SG8 ENCLOSED SKILLION ROOF H1.2 KD SG8 TRUSS FRAMING H1.2 KD SG8 LVL MEMBERS H3.2 PURLINS H1.2 KD SG8 RIDGE AND HIPS H1.2 KD SG6 VALLEY BOARDS H1.2 KD SG6

EXTERIOR WALLS H1.2 KD SG8 EXTERIOR WALLS LINTELS H1.2 KD SG8 LVL LINTELS H3.2 **CAVITY BATTENS H3.1** INTERIOR WALLS H1.2 KD SG8 WET AREA WALLS H1.2 KD SG8

LANDSCAPING: FENCE PALINGS BATTENS & RAILS H3.2 WET SG6 FENCE POST H4 WET SG6 **RETAINING POLES H5 WET SG6** RETAINING RAILS H4 WET SG6

ENCLOSED DECKS: ENCLOSED POST & BEAMS H3.2 SG8 **CAVITY BATTENS H3.1** FRAMING & NOGS H1.2 SG8

217/03/2024

EXTERIOR - SG8 H1.2 TIMBER FRAMING, STUDS @400 CTRS,NOGGS @600CRS MAX

EXTERIOR - SG8 H1.2 TIMBER FRAMING, STUDS @400 CTRS, NOGGS @800CRS MAX

INTERIOR - 90 MM X 45 MM TIMBER FRAMING, STUDS @600 CTRS AND NOGGS @800 CTRS,

TF4 LBW - 90X45MM SG8 H1.2 TIMBER STUDS @400 CTRS MAX, 10MM THK GIB BOTH SIDES

TIMBER TRUSSES SG8 H1.2 @ 900 CRS. MAX. REFER TO TRUSS DESIGN DOCUMENTS

TIMBER RAFTER SG8 H1.2 @ 900 CRS. MAX., REFER TO STRUCTURAL **ENGINEERS DRAWING**

11 R2.0 WALL INSULATION

| 12 | R7.0 CEILING INSULATION

R5.3 PODS INSULATION

EXTERNAL WALL

10MM GIB LINING

CEILING BATTENS

TO MANUFACTURER

TIMBER TRUSSES

SPECIFICATIONS

100MM LONG

DETAIL

RAFTERS

SPECIFICATIONS FOR SEA SPRAY ZONE

REFER TO STRUCTURAL DRAWINGS &

H1.2 70X45MM ON FLAT @900 CTRS MAX.

600MM CRS MAX (@ END SPAN)

900MM CRS MAX (@ INTERMEDIATE SPAN)

REFER TO TRUSS MANUFACTURER'S LAYOUT AND

FIXED WITH 1/14G TYPE 17 SELF DRILLING SCREW,

SG8 H1.2 70X35MM TIMBER CEILING BATTENS AT 450

CTRS MAX FIXED WITH POWER DRIVEN NAILS OVER

90X45MM SG8 H1.2 TIMBER FRAMING ON 20X40MM H3.1 DRAINED AND VENTED CAVITY BUILDING UNDERLAY AND INSULATION AS SPECIFIED 2.4M HT STUDS @600CRS MAX 2.7M HT STUDS @400CRS MAX **NOGGINGS**

70S BRICK CLADDING @ 800CRS MAX LINEA OBLIQUE VERTICAL @ 600CRS MAX

INTERNAL WALL

90X45MM SG8 H1.2 TIMBER FRAMING AT 800 CRS MAX

LOAD BEARING WALL (LBW)

90X45MM SG8 H1.2 TIMBER FRAMING AT 400 CRS MAX BOTTOM PLATES SG8 H1.2 TIMBER FRAMING

INTERIOR LININGS

DRY AREAS WALL GIB STANDARD 10 MM CEILING GIB STANDARD 10 MM WET AREAS WALLS GIB AQUALINE 10 MM CEILING GIB AQUALINE 10 MM

THERMAL INSULATION

CEILING PINK BATTS ROOF INSULATION R 7.0 PINK BATTS WALL INSULATION R 2.0 **ALUMINIUM JOINERY** TO BE LOW-E DOUBLE GLAZED R0.46 FI OOR KOOLFOAM ECO PODS R5.3

WET AREAS
WATERPROOFING MEMBRANE ARDEX WPM SYSTEM INSTALLED TO MANUFACTURER'S SPECIFICATION

UNDERLAYS

THERMAKRAFT COVERTEK 407 WALL MARSHALL TEKTON SUPERCOURSE 500™ DPC THERMAKRAFT THERMATHENE ORANGE™ 300

CONCRETE FOUNDATION FOUNDATION TO ENGINEER'S DESIGN

TIMBER GRADES

ALL TIMBER TO BE TREATED AND GRADED AS FOLLOWS UNLESS OTHERWISE NOTED ON DRAWINGS: SG8 GRADE. H1.2 TREATED TOP PLATE: SG8 GRADE, H1.2 TREATED LINTEL:

SG8 GRADE, H1.2 TREATED BOTTOM PLATE: SG8 GRADE, H1.2 TREATED TOP PLATE TO STUD FIXING 2/90 X 3.15 END NAILS + 2 WIRE DOGS

TOP/ BOTTOM PLATES

TOP & BOTTOM PLATES TO BE SG8 90 X 45 ALLOW DPC BETWEEN TIMBER AND CONCRETE; TIMBER AND STEEL

DATE DESCRIPTION **BUILDING CONSENT** SILICON ARCHITECTURE

Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55 www.siliconarchitecture.com admin@siliconec.co.nz

© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted

STONEX HOMES

PROJECT

PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

CONSTRUCTION NOTES

SCALE AT A3: DATE ISSUE: CHECKED: As indicated 4/03/2024 12:07:56 pm KK-JP REVISION: 1944 A004

SPACING SHALL BE A MAXIMUM OF 2.5 M, AND THE GAP BETWEEN THE BOTTOM OF 105 FT 15996 Received by Auckland Council 07/03/2024 GROUND NO GREATER THAN 100 MM.

PROPERTY DETAILS
LEGAL DESCRIPT Frage 16 of 735 Building Consent BCO10375996 Approved by Auckland Council ADDRESS: 8 GERTRUDE COLE ROAD CLARKS BEACH ROAD PUKEKOHE AUCKLAND 2679 PROPERTY AREA: 487SQM **RESIDENTIAL - MIXED HOUSING SUBURBAN** ZONE: PRECINCT: **CLARKS BEACH** WIND AREA: HIGH WIND ZONE **LEGEND** PROPERTY BOUNDARY EXTG WASTE WATER LINE EXTG STORM WATER LINE **EXISTING STRUCTURE** 136 **EXISTING CONCRETE** LT 573987 11=1943 SWMH LL=19.45 IL=17.95(100ø) IL=17.44(Out) SW Conn 143°13'30" 31.40 Top of Kerb Road 54°08'00" LOT 137 LT 573987 Cole 55°53'00" 26 ري. دي. DP **Sertrude** 567326 VEHICLE CROSSING 144°38'00' 31.86 138 LT 573987 **EXISTING SITE PLAN** A301 1:150 @ A3

24/03/2024

SITE BOUNDARY DIMENSIONS AND BEARINGS HAVE BEEN IMPORTED FROM CADASTRAL SURVEY

ALL CONSTRUCTION TO COMPLY WITH NZBC & NZS 3604:2011 THE CONTRACTOR SHALL BE RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL DIMENSIONS AND FLOOR LEVELS PRIOR TO COMMENCING WORK. SITE BOUNDARIES, BUILDING FLOOR LEVELS & PROFILES TO BE PROVIDED & SETOUT BY A REGISTERED SURVEYOR. THE CONTRACTOR WILL BE SOLELY RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL UNDERGROUND SERVICES PRIOR TO COMMENCEMENT OF WORK INCLUDING GRADIENTS, FALLS, CONNECTION POINTS AND SIZES.

ALL DISCREPANCIES TO BE RAISED PRIOR TO COMMENCING ANY WORK. DO NOT SCALE FROM THESE DRAWINGS, WORK FROM DIMENSIONS.

CONTRACTOR TO NOTIFY SILICON ARCHITECTURE OF ANY DISCREPANCIES

FLAG DRAINS AND MANHOLES PRIOR TO COMMENCING.

DESCRIPTION **BUILDING CONSENT** Bldg. 8 Level 1, 15 Accent Drive East

Tamaki Auckland, New Zealand admin@siliconec.co.nz

© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted

STONEX HOMES

PROJECT


PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

EXISTING SITE PLAN

SCALE AT A3: DATE ISSUE: As indicated 4/03/2024 12:07:59 pm DESIGN: KK-JP 1944 A100

BCO10375996 Received by Auckland Council 07/03/2024



21/03/2024

SITE BOUNDARY DIMENSIONS AND BEARINGS HAVE BEEN IMPORTED FROM CADASTRAL SURVEY

ALL CONSTRUCTION TO COMPLY WITH NZBC & NZS 3604:2011 THE CONTRACTOR SHALL BE RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL DIMENSIONS AND FLOOR LEVELS PRIOR TO COMMENCING WORK. SITE BOUNDARIES, BUILDING FLOOR LEVELS & PROFILES TO BE PROVIDED & SETOUT BY A REGISTERED SURVEYOR. THE CONTRACTOR WILL BE SOLELY RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL UNDERGROUND SERVICES PRIOR TO COMMENCEMENT OF WORK INCLUDING GRADIENTS, FALLS, CONNECTION POINTS AND SIZES.

ALL DISCREPANCIES TO BE RAISED PRIOR TO COMMENCING ANY WORK. DO NOT SCALE FROM THESE DRAWINGS, WORK FROM DIMENSIONS.

CONTRACTOR TO NOTIFY SILICON ARCHITECTURE OF ANY DISCREPANCIES

FLAG DRAINS AND MANHOLES PRIOR TO COMMENCING.

1 CHANGE: FFL UPDATED 25/01/2024
REV DESCRIPTION DATE

STATUS: BUILDING CONSENT

ARCHITECTURE

Bldg. 8 Level 1, 15 Accent Drive East

dg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55 www.siliconarchitecture.com admin@siliconec.co.nz

© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited.

This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted.

CLIENT:

STONEX HOMES

PROJECT:

PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

PROPOSED SITE PLAN

BCO10375996 Received by Auckland Council 07/03/2024

PROPERTY DETAILS LEGAL DESCRIPT Frage 18 of 735 Building Consent BCO10375996 Approved by Auckland Council ADDRESS: 8 GERTRUDE COLE ROAD CLARKS BEACH ROAD PUKEKOHE AUCKLAND 2679 PROPERTY AREA: 487SQM **RESIDENTIAL - MIXED HOUSING SUBURBAN** ZONE: PRECINCT: **CLARKS BEACH** WIND AREA: HIGH WIND ZONE **LEGEND** 4000 OUTLOOK SPACE 00 (1mX1m) **DUTLOOK SPACE** (3mX3m) OUTLOOK SPACE OUTDOOR LIVING SPACE (4mX5m) 20SQM FRONT YARD LANDSCAPE AREA 4000 OUTDOOR LIVING (1mX1m) (1mX1m) (3mX3m) OUTLOOK SPACE (4mX6m)

1

A102

1:150 @ A3

24103/2024

SITE BOUNDARY DIMENSIONS AND BEARINGS HAVE BEEN IMPORTED FROM CADASTRAL SURVEY

ALL CONSTRUCTION TO COMPLY WITH NZBC & NZS 3604:2011 THE CONTRACTOR SHALL BE RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL DIMENSIONS AND FLOOR LEVELS PRIOR TO COMMENCING WORK. SITE BOUNDARIES, BUILDING FLOOR LEVELS & PROFILES TO BE PROVIDED & SETOUT BY A REGISTERED SURVEYOR. THE CONTRACTOR WILL BE SOLELY RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL UNDERGROUND SERVICES PRIOR TO COMMENCEMENT OF WORK INCLUDING GRADIENTS, FALLS, CONNECTION POINTS AND SIZES.

ALL DISCREPANCIES TO BE RAISED PRIOR TO COMMENCING ANY WORK. DO NOT SCALE FROM THESE DRAWINGS, WORK FROM DIMENSIONS.

CONTRACTOR TO NOTIFY SILICON ARCHITECTURE OF ANY DISCREPANCIES

FLAG DRAINS AND MANHOLES PRIOR TO COMMENCING.



© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of

reproduction is not permitted

STONEX HOMES


PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

OUTLOOK/OUTDOOR/TRACKING

As indicated 4/03/2024 12:08:04 pm KK-JP ROJECT NO A102

Gertrude Cole Road



PROPERTY DETAILS LEGAL DESCRIPT Frage 19 of 735 Building Consent BCO10375996 Approved by Auckland Council ADDRESS: 8 GERTRUDE COLE ROAD CLARKS BEACH ROAD PUKEKOHE AUCKLAND 2679 PROPERTY AREA: 487SQM **RESIDENTIAL - MIXED HOUSING SUBURBAN** ZONE: PRECINCT: **CLARKS BEACH** WIND AREA: HIGH WIND ZONE

LEGEND

EXTG WW'

-EXTG SW'-

PROPERTY BOUNDARY

INTERNAL BOUNDARY

EXTG WASTE WATER LINE

EXTG STORM WATER LINE

PROPOSED STRUCTURE

PRIVATE WASTE WATER LINE

PRIVATE STORMWATER LINE



24103/2024

SITE BOUNDARY DIMENSIONS AND BEARINGS HAVE BEEN IMPORTED FROM CADASTRAL SURVEY

ALL CONSTRUCTION TO COMPLY WITH NZBC & NZS 3604:2011 THE CONTRACTOR SHALL BE RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL DIMENSIONS AND FLOOR LEVELS PRIOR TO COMMENCING WORK. SITE BOUNDARIES, BUILDING FLOOR LEVELS & PROFILES TO BE PROVIDED & SETOUT BY A REGISTERED SURVEYOR. THE CONTRACTOR WILL BE SOLELY RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL UNDERGROUND SERVICES PRIOR TO COMMENCEMENT OF WORK INCLUDING GRADIENTS, FALLS, CONNECTION POINTS AND SIZES.

ALL DISCREPANCIES TO BE RAISED PRIOR TO COMMENCING ANY WORK. DO NOT SCALE FROM THESE DRAWINGS, WORK FROM DIMENSIONS.

CONTRACTOR TO NOTIFY SILICON ARCHITECTURE OF ANY DISCREPANCIES

FLAG DRAINS AND MANHOLES PRIOR TO COMMENCING.



LOT 137, 8 GERTRUDE COLE ROAD

CLARKS BEACH, PUKEKOHE


PROPOSED SITE DRAINAGE PLAN


A103

SCALE AT A3: DATE ISSUE:

1944

As indicated A/03/2024 12:08:05 pm DESIGN: KK-JP





24/03/2024


SITE BOUNDARY DIMENSIONS AND BEARINGS HAVE BEEN IMPORTED FROM CADASTRAL SURVEY

ALL CONSTRUCTION TO COMPLY WITH NZBC & NZS 3604:2011 THE CONTRACTOR SHALL BE RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL DIMENSIONS AND FLOOR LEVELS PRIOR TO COMMENCING WORK. SITE BOUNDARIES, BUILDING FLOOR LEVELS & PROFILES TO BE PROVIDED & SETOUT BY A REGISTERED SURVEYOR. THE CONTRACTOR WILL BE SOLELY RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL UNDERGROUND SERVICES PRIOR TO COMMENCEMENT OF WORK INCLUDING GRADIENTS, FALLS, CONNECTION POINTS AND SIZES.

ALL DISCREPANCIES TO BE RAISED PRIOR TO COMMENCING ANY WORK. DO NOT SCALE FROM THESE DRAWINGS, WORK FROM DIMENSIONS.

CONTRACTOR TO NOTIFY SILICON ARCHITECTURE OF ANY DISCREPANCIES

FLAG DRAINS AND MANHOLES PRIOR TO COMMENCING.



BUILDING CONSENT



Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55 admin@siliconec.co.nz

© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted

STONEX HOMES

PROJECT

PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

PROPOSED SITE SEDIMENT PLAN

SCALE AT A3: DATE ISSUE: CALE AT A3: DATE ISSUE: DESIGN:
As indicated 4/03/2024 12:08:09 pm KK-JP 1944 A104


PROPERTY DETAILS
LEGAL DESCRIPT Hage 11/1 of 35 Building Consent BCO10375996 Approved by Auckland Council ADDRESS: 8 GERTRUDE COLE ROAD CLARKS BEACH ROAD

PUKEKOHE AUCKLAND 2679

PROPERTY AREA: 487SQM ZONE:

RESIDENTIAL - MIXED HOUSING SUBURBAN

PRECINCT: **CLARKS BEACH** WIND AREA: **HIGH WIND ZONE**



SITE SLAB SETOUT A105 1:150 @ A3

Road Cole Gertrude

24/03/2024

SITE BOUNDARY DIMENSIONS AND BEARINGS HAVE BEEN IMPORTED FROM CADASTRAL SURVEY

ALL CONSTRUCTION TO COMPLY WITH NZBC & NZS 3604:2011 THE CONTRACTOR SHALL BE RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL DIMENSIONS AND FLOOR LEVELS PRIOR TO COMMENCING WORK. SITE BOUNDARIES, BUILDING FLOOR LEVELS & PROFILES TO BE PROVIDED & SETOUT BY A REGISTERED SURVEYOR. THE CONTRACTOR WILL BE SOLELY RESPONSIBLE TO LOCATE, CHECK & VERIFY ALL UNDERGROUND SERVICES PRIOR TO COMMENCEMENT OF WORK INCLUDING GRADIENTS, FALLS, CONNECTION POINTS AND SIZES.

ALL DISCREPANCIES TO BE RAISED PRIOR TO COMMENCING ANY WORK. DO NOT SCALE FROM THESE DRAWINGS, WORK FROM DIMENSIONS.

CONTRACTOR TO NOTIFY SILICON ARCHITECTURE OF ANY DISCREPANCIES

FLAG DRAINS AND MANHOLES PRIOR TO COMMENCING.

DESCRIPTION **BUILDING CONSENT**

Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55 www.siliconarchitecture.com admin@siliconec.co.nz

© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted

STONEX HOMES

PROJECT

PROPOSED RESIDENCE


LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

PROPOSED SITE PLAN - SLAB SETOUT SCALE AT A3: DATE ISSUE:

As indicated 4/03/2024 12:08:10 pm KK-JP PROJECT NO 1944 A105


Page 12 of 35 Building Consent BCO10375996 Approved by Auckland Council








S SMOKE ALARM





FLOOR AREA: 194.67 SQM

TOTAL:

194.67 SQM



LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

GROUND FLOOR PLAN

DATE ISSUE: DESIGN: 4/03/2024 12:08:11 pm KK-JP PROJECT NO 3 1944 A201

TAYLOR CLA Page 13 of 35 M Building Consent BCO10375996 Approved by Auckland Council

The 125mm is a colonial style profile. It is tried and true and is suitable for most homes. The
150mm is a similar profile. It is a high capacity gutter and is a great alternative to a box gutter.

Sizes: 125mm, 150mm

Material: COLORSTEEL® Endura® / Maxx®, ZR8™/ZRX™, 0.50mm Copper
Capacity: 5800mm2, 10,000mm2


Duilding envelope (as recommended in BRANZ Technical Builetin Issue 509, "Sizing Gutters and

building envelope (as recommended in BRANZ Technical Bulletin Issue 509, "Sizing Gutters and Downpipes", Clause 4.01).

Spouting Capacity:

Rainfall Intensity* 40 50 60 70 80 90 100 110 120 130 140 150 (mm/hr)
Maximum Catchment 146 117 97 83 73 65 58 53 49 45 42 39

**As per NZBC E1 – Surface Water, Rainfall Intensity equates to a 1 in 10 year storm and varies depending on geographic location For example, 100mm/hr is a general rule of thumb for the Auckland region however please refer to hirds nive on z for current



21/03/2024 ROOFING NOTES:

WIND ZONE: HIGH



STRUCTURAL ENGINEER TO ENSURE ALL LINTELS AND BEAMS ARE SIZED FOR THE LOADS APPLIED BY THE TRUSS/RAFTERS IN LAYOUT ENSURE ALL INTERNAL LOAD BEARING WALLS HAVE THE CORRECT SLAB THICKENING

ROOFING MATERIAL

TRS 5 0.55BMT LONG RUN METAL ROOFING WITH ROOF UNDERLAY INSTALL TO MANUFACTURER SPECIFICATIONS FIXING: 12G X 65MM OR 14G X 75MM WITH LOAD SPREADING WASHER ("D" FIXING PATTERN)

PURLINS

H1.2 70X45MM ON FLAT @900 CTRS MAX. 900MM CRS MAX (@ INTERMEDIATE SPAN) 600MM CRS MAX (@ END SPAN) FIXED WITH 1/14G TYPE 17 SELF DRILLING SCREW, 100MM LONG

ROOFING SYSTEM

TIMBER TRUSSES - TO MANUFACTURERS DESIGN AND SPECIFICATIONS

RAFTERS - TO STRUCTURAL ENGINEER DESIGN AND SPECIFICATIONS

CEILING BATTENS

SG8 H1.2 70X35MM SPACE @ 600 CTRS MAX FIXED WITH POWER DRIVEN NAILS

OWNPIPES

IN COMPLIANCE WITH NZBC E1/AS1, 1 OF 80Ø DP PER 85M² ROOF PLAN AREA - PITCH 0-25° AS PER TABLE 5

ROOF BRACING


LUMBERLOK STRAP BRACING - INSTALL TO MANUFACTURERS SPECIFICATION IN ACCORDANCE WITH NZS 3604:2011 SECT. 10.3 - REFER TO ENGINEERING DOCUMENTS FOR BRACING ELEMENTS & CALCULATIONS

| CALCUL | LATIONS | | |
|-------------|--|-------------------------------------|---|
| REV | DESCRIPTION | DATE |] |
| STATUS: | BUILDING CONSE | NT | 2.28.rvt |
| Ы | SILIC(| DN URE | GERTRUDE_BC-2_24.02 |
| Tama | Level 1, 15 Accent Drive East aki Auckland, New Zealand PH: 09 265 19 55 w.siliconarchitecture.com admin@siliconec.co.nz | | RENT CADILOT 137, 8 GERTRUDE COLEILOT137_8 GERTRUDE_BC-2_24.02.28.m |
| Th Archi | right 2023. This design shall re with Silicon Architecture Lim is drawing remains the property tecture Limited & may not reprc tten permission of Silicon Archit | ited. of Silicon duce without | RENT CAD/LOT 137,8 C |

| the writte The infor | n permi mation of cont | ssion of S contain in tractor & I | | hitecture of drawing Any type | Limited. s are to | |
|-------------------------|------------------------------|---|---------|-------------------------------------|----------------------|---|
| LIENT: | | | | | | ľ |
| | STO | ONEX | HOM | 1ES | | |
| PROJECT: | | | | | | |
| Р | ROP | OSED | RESID | ENCE | | |
| ITE: | | | | | | 1 |
| | | | RUDE C | | | |
| | LARK | S BEAC | H, PUK | EKOHE | | |
| TTLE: | | | | | | |
| | PRO | POSED | ROOF I | PLAN | | |
| CALE AT A3: | DATE ISS | | DESIGN: | DRAWN: | CHECKED: | |
| 1:100 | 4/03/2024 | 12:08:13 pm | KK-JP | J | | |
| | | | | | | |

A202

1944





24/03/2024

TV TERMINAL VENT
GT GULLY TRAP
ST STACK
IB INSPECTION BEND
IJ INSPECTIONT JOINT
AAV AIR ADMITTANCE VALVE
DP DOWNPIPE
ST SILT TRAP
AP ACCESS POINT
FWG FLOOR WASTE GULLY
VTR VENT THRU ROOF
MECHANICAL VENT/FAN
STORMWATER LINE
SANITARY SEWER LINE

NOTE: ALLOW TO SUPPLY HOT WATER AND/OR COLD WATER TO ALL FITTINGS USING 15MM DIAMETER POLYBUTYLENE PIPEWORK UNLESS OTHERWISE NOTED.

FAN EXTRACTION NOTES:
BATHROOM - TO ACHIEVE 25L/S
EXTRACTION
LAUNDRY - TO ACHIEVE 20L/S WITH
CONDENSING DRYER AND 40L/S WITH
NON-CONDENSING DRYER AND 50L/S
FOR COOKTOPS

ACCIDENTAL OVERFLOW FROM SANITARY APPLIANCES SUCH AS A DISH WASHER OR THE WASHING MACHINE CAN BE MITIGATED WHERE APPLIANCES HAVE AN AUTOMATIC SHUT OFF MECHANISM BUILT IN WHICH WILL PREVENT THE APPLIANCE FROM OVERFLOWING.



Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55 www.siliconarchitecture.com admin@siliconec.co.nz

© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited.

This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted.



PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

PROPOSED PLUMBING LAYOUT

 SCALE AT A3:
 DATE ISSUE:
 DESIGN:
 DRAWN:
 CHECKED:

 1:100
 4/03/2024 12.08:14 pm
 KK-JP
 J
 CHECKED:

 PROJECT NO:
 DRAWING NO:
 REVISION:

 1944
 A203
 REVISION:

GENERAL NOTES Page 15 of STERN BY AUDITOR CONSENT BC CHERN STERN BY SERVING AT 600 CRS MAX CEILING PINK BATTS ROOF INSULATION TO ENGINEER'S DESIGN

METALCRAFT - 0.55BMT METAL LONG RUN **ROOFING - INSTALL TO MANUFACTURER** SPECIFICATIONS

REFER TO TRUSS MANUFACTURER'S LAYOUT AND DETAIL

REFER TO STRUCTURAL DRAWINGS & **SPECIFICATIONS**

H1.2 70X45MM ON FLAT @900 CTRS MAX. 900MM CRS MAX (@ INTERMEDIATE SPAN) 600MM CRS MAX (@ END SPAN) FIXED WITH 1/14G TYPE 17 SELF DRILLING SCREW, 100MM LONG

CEILING BATTENS

SG8 H1.2 70X35MM TIMBER CEILING BATTENS AT 400 CTRS MAX FIXED WITH POWER DRIVEN NAILS OVER 10MM GIB

C

D

G

1:100@A3

A402

A402

A204

1180

∠8∤

1000

WALL SET-OUT AND REFERENCE PLAN

5790 10150

ON 20X40MM H3.1 DRAINED AND VENTED CAVITY BUILDING UNDERLAY AND INSULATION AS SPECIFIED

INTERNAL WALL

90X45MM SG8 H1.2 TIMBER FRAMING AT 800 CRS MAX

LOAD BEARING WALL (LBW)

90X45MM SG8 H1.2 TIMBER FRAMING AT 400 CRS MAX **BOTTOM PLATES SG8 H1.2 TIMBER FRAMING**

70S BRICK CLADDING @ 800CRS MAX LINEA OBLIQUE VERTICAL @ 600CRS MAX

INTERIOR LININGS

DRY AREAS WALL GIB STANDARD 10 MM CEILING GIB STANDARD 10 MM WET AREAS WALLS GIB AQUALINE 10 MM **CEILING GIB AQUALINE 10 MM**

4120

4030

SD1 2200x2000

WIW

4120

1015

ENSUITE

600x2000

MASTER

BEDROOM 1

R 7 0

WALLS PINK BATTS ULTRA WALL INSULATION

GLAZING POWER COATED ALUMINIUM JOINERY TO BE DOUBLE GLAZED R0.26

FLOOR KOOLFOAM ECO PODS R5.3

WET AREAS

WATERPROOFING MEMBRANE MAPEI MAPEGUM WPS SYSTEM INSTALLED TO MANUFACTURER'S SPECIFICATION

SUBSTRATES: 17MM PLYWOOD MIN COMPLYING WITH AS/NZS 2269, F11, CD GRADE STRUCTURAL WITH SANDED C FACE UP AND H3.2 TREATED. DO NOT USE LOSP

COMMON AREAS: 20MM THK PARTICLE BOARD

8360

2000

W5

BATHROOM

910

1090

90,

645

3000

W2

BEDROOM 2

1100

1900

THERMAKRAFT COVERTEK 407 WALL MARSHALL TEKTON

SUPERCOURSE 500™ DPC

THERMAKRAFT THERMATHENE ORANGE™ 300

23240

3090

W1 1200x1800

BEDROOM 3

1100

1990

3

W4 2200x800

KITCHEN

1075

900

TIMBER GRADES

ALL TIMBER TO BE TREATED AND GRADED AS FOLLOWS UNLESS OTHERWISE NOTED ON

DRAWINGS:

TOP PLATE: SG8 GRADE, H1.2 TREATED SG8 GRADE, H1.2 TREATED LINTEL: SG8 GRADE, H1.2 TREATED STUDS: BOTTOM PLATE: SG8 GRADE, H1.2 TREATED

TOP PLATE TO STUD FIXING 2/90 X 3.15 END NAILS + 2 WIRE DOGS

TOP/ BOTTOM PLATES

TOP & BOTTOM PLATES TO BE SG8 90 X 45

ALLOW DPC BETWEEN TIMBER AND CONCRETE; TIMBER AND STEEL

A401

10760

10575

W3 2200x60

2015

SD1 2200x2000

DINING

DOWNLIGHT NOTES

7.4.1 IN RESIDENTIAL OCCUPANCIES, RECESSED LUMINARIES SHALL BE ON OF THE FOLLOWING TYPES, AS SPECIFIED IN AS/NZS 60598.2.: (a) IC-F, or

(b) IC or (c) CA-80 or (d) CA-135

4 5

W3 2200x60

2800

LOUNGE

6

W3

2200x60

W3_ 200x60

FULL COMPLIANCE CAN ONLY BE ACHIEVED IF THE INSTALLATION OF THE LUMINAIRE IN ACCORDANCE WITH AS/ NZS 60598.2.2

21/03/2024 ALL TIMBER MATERIALS SHALL COMPLY WITH CURRENT NEW ZEALAND STANDARDS 3602:2003

ALL MATERIALS/BUILDING COMPONENTS (ROOFING, CLADDING, WINDOWS, DOORS **ETC) TO BE INSTALLED IN STRICT** ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS & INSTALLATION DETAILS. IF THE CONTRACTOR IS IN ANY DOUBT CONTACT THE MANUFACTURER PRIOR TO CONSTRUCTION

FIXING NOTES

ALL FIXINGS TO COMPLY WITH NZS 3604:2011 SECTION 4 AND IN PARTICULAR SECTION 4.4 TO ENSURE BUILDING CODE COMPLIANCE REFER TO NZS 3604:2011 SECTION 4 TABLE 4.1 FOR PROTECTION REQUIRED FOR STEEL FIXINGS AND FASTENINGS EXCLUDING NAILS AND SCREWS.


- STRUCTURAL FIXINGS TO ALL BE 304 STAINLESS STEEL AS IF SITE IS IN ZONE D REFER TO TABLE 4.1 AND 4.3, NZS3604


SAFETY NOTES SMOKE ALARMS TO BE INSTALLED THROUGHOUT THE DWELLING TO COMPLY WITH NZBC F7/AS1 SECTION 3.1 TO 3.3. FITTED WITH HUSH FACILITY AS REQUIRED. ENSURE 300MM MIN FROM WALLS, 3M MAX FROM BEDROOM DOORS

STAIR TREAD AND RISER HEIGHT TO COMPLY WITH NZBC D1/AS1 - 190MM MAX RISER, 280 MIN TREAD. SEE TABLE 6 AND FIGURES 12&13 GRASPABLE HANDRAILS TO BE INSTALLED 900MM ABOVE FFL AS PER D1/AS1 MINIMUM SLIP RESISTANCE TO STEPS AND LANDINGS IN ACCORDANCE WITH NZBC D1/AS1

VENTILATION MECHANICAL VENTILATION TO BE INSTALLED IN EVERY BATHROOM AND KITCHEN AREA IN

ACCORDANCE WITH G4/AS1





Bldg, 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55

admin@siliconec.co.nz © Copyright 2023. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited.

The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted

STONEX HOMES


PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE WALL SETOUT PLAN

SCALE AT A3: DATE ISSUE: 4/03/2024 12:08:16 pm KK-JP 1:100 EVISION:

A204


3





Page 16 of 35 Building Consent BCO10375996 Approved by Auckland Council

EXTERIOR FINISH LEGENDS:

LINEA OBLIQUE VERTICAL (300MM) CLADDING ON 20MM CAVITY









217/08/2024

- EXTERIOR SG8 H1.2 TIMBER FRAMING, STUDS @400 CTRS,NOGGS @600CRS MAX
- EXTERIOR SG8 H1.2 TIMBER FRAMING, STUDS @400 CTRS, NOGGS @800CRS MAX
- INTERIOR 90 MM X 45 MM TIMBER FRAMING, STUDS @600 CTRS AND NOGGS @800 CTRS,
- TF4 LBW 90X45MM SG8 H1.2 TIMBER STUDS @400 CTRS MAX, 10MM THK GIB BOTH SIDES
- RF1 TIMBER TRUSSES SG8 H1.2 @ 900 CRS. MAX, REFER TO TRUSS DESIGN DOCUMENTS
- TIMBER RAFTER SG8 H1.2 @ 900 CRS. MAX., REFER TO STRUCTURAL **ENGINEERS DRAWING**
- I1 R2.0 WALL INSULATION
- 12 R7.0 CEILING INSULATION
- 13 R5.3 PODS INSULATION

DOWNLIGHT NOTES

7.4.1 IN RESIDENTIAL OCCUPANCIES, RECESSED LUMINARIES SHALL BE ON OF THE FOLLOWING TYPES, AS SPECIFIED IN AS/NZS 60598.2.: (a) IC-F, or

- (b) IC, or
- (c) CA-80 or (d) CA-135

FULL COMPLIANCE CAN ONLY BE ACHIEVED IF THE INSTALLATION OF THE LUMINAIRE IN ACCORDANCE WITH AS/ NZS 60598.2.2



LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

WALL REFERENCE PLAN


A205

DATE ISSUE: DESIGN: 4/03/2024 12:08:18 pm KK-JP

PROJECT NO

1944





EXTERIOR FINISH LEGENDS:

F1


LINEA OBLIQUE VERTICAL (300MM) CLADDING ON 20MM CAVITY



70S BRICK CLADDING ON 50MM CAVITY



TRS 5, 0.55 BMT METAL LONG RUN ROOFING OVER PURLINS



NORTH ELEVATION

1:100@A3

A301

| Part of Building | North Elevation | | | | |
|-------------------------------|-----------------|-------|--|--|--|
| Risk Factor | Risk severity | Score | | | |
| Wind Zone | HIGH | 1 | | | |
| Number of storeys | LOW | 0 | | | |
| Roof/wall intersection design | LOW | 0 | | | |
| Eaves width | HIGH | 2 | | | |
| Envelope complexity | MEDIUM | 1 | | | |
| Deck design | LOW | 0 | | | |
| Total risk score | North Elevation | 4 | | | |

| Part of Building | East Elevation | | | | | |
|-------------------------------|----------------|-------|--|--|--|--|
| Risk Factor | Risk severity | Score | | | | |
| Wind Zone | HIGH | 1 | | | | |
| Number of storeys | LOW | 0 | | | | |
| Roof/wall intersection design | LOW | 0 | | | | |
| Eaves width | HIGH | 2 | | | | |
| Envelope complexity | MEDIUM | 1 | | | | |
| Deck design | LOW | 0 | | | | |
| Total risk score | East Elevation | 4 | | | | |



© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited.

This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of

CLIENT:

STONEX HOMES

reproduction is not permitted

PROJECT:


PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

PROPOSED ELEVATIONS

| CHECKED | | DRAWING NO: | REVISION | 1944 | A301 | A301





| Part of Building | West Elevation | | | | | |
|-------------------------------|----------------|-------|--|--|--|--|
| Risk Factor | Risk severity | Score | | | | |
| Wind Zone | HIGH | 1 | | | | |
| Number of storeys | LOW | 0 | | | | |
| Roof/wall intersection design | LOW | 0 | | | | |
| Eaves width | HIGH | 2 | | | | |
| Envelope complexity | MEDIUM | 1 | | | | |
| Deck design | LOW | 0 | | | | |
| Total risk score | West Elevation | 4 | | | | |



(300MM) CLADDING ON 20MM CAVITY

70S BRICK CLADDING ON 50MM CAVITY

TRS 5, 0.55 BMT METAL LONG RUN ROOFING OVER PURLINS



reproduction is not permitted STONEX HOMES

PROPOSED RESIDENCE


The information contain in this set of drawings are to

use of contractor & LTA only. Any type of


LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

PROPOSED ELEVATIONS

CALE AT A3: DATE ISSUE: DESIGN: KK-JP PROJECT NO A302 1944



| 2 | WEST ELEVATION | |
|------|----------------|--|
| A302 | 1 : 100 @ A3 | |



PEXTERNAL SLAZING NOTE

ALL GLAZING TO COMPLY WITH F2/AS1 1.0 GLAZING AND NZS4223.3: 2016 PARTS 1.3. WINDOW OPENINGS TO COMPLY WITH F4/AS1 - CLAUSE 2.0 OPENING WINDOWS. (APPLY WHERE THE POSSIBLE HEIGHT OF FALL FROM OPENING WINDOW IS MORE THAN 1000MM. (THE HEIGHT OF FALL SHALL BE MEASURED FROM THE INSIDE FLOOR LEVEL ADJACENT TO THE WINDOW).

ALLOW TO PROVIDE RESTRICTOR (R) STAYS TO WINDOWS LESS THAN 1.0 WIDE WITH SILL HEIGHTS LESS THAN 760mm ABOVE FINISHED FLOOR LEVEL IN ACCEPTANCE WITH NZBC F2/AS1.

OPENING LESS THAN 1000MM WIDE SHALL HAVE; EITHER -

A) THE LOWER EDGE OF THE OPENING AT LEAST 760MM ABOVE FLOOR LEVEL, OR B) A RESTRICTOR FITTED TO LIMIT THE MAX. OPENING SO THAT A 100MM DIAMETER SPHERE CANNOT PASS THROUGH IT.

OPENING GREATER THAN 1000MM WIDE SHALL HAVE -A) THE LOWER EDGE OF THE OPENING AT A HEIGHT MIN. 1000MM ABOVE FLOOR

WINDOW MANUFACTURER SHALL CHECK ON SITE ALL WINDOW OPENING SIZES PRIOR TO ASSEMBLY. ALL GLAZING TO BE LOW-E DOUBLE GLAZED ALUMINIUM JOINERY 4mm GLASS / 12mm CAVITY / 4mm GLASS WITH AN SRI VALUE OF 56 OR OTHERWISE NOTED.

SAFETY GLASS NOTE:

SAFETY GLASS (SG) TO WINDOWS & SHOWERS LOCATED IN THE ENSUITE & BATHROOM& WINDOWS WITHIN 800MM OF THE FLOOR.

| 1 CHA | NGE: FFL UPDATED | 25/01/2024 |
|-----------------------------|---|---|
| REV | DESCRIPTION | DATE |
| STATUS: | BUILDING CONSE | NT |
| | SILIC(| DN URE |
| Tama | evel 1, 15 Accent Drive East ki Auckland, New Zealand PH: 09 265 19 55 v.siliconarchitecture.com dmin@siliconec.co.nz | |
| Thi Archite the writt | right 2023. This design shall re with Silicon Architecture Lin s drawing remains the property ecture Limited & may not repro- en permission of Silicon Archit ormation contain in this set of c see of contractor & LTA only. Ar reproduction is not permitt | nited. y of Silicon oduce without ecture Limited. Irawings are to ny type of |
| CLIENT: | STONEX HOME | ES |

CT:

DDOD

PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

DOORS & WINDOWS SCHEDULE

 SCALE AT A3:
 Date ISSUE:
 DESIGN:
 DRAWN:
 CHECKED:

 As indicated
 4/03/2024 12:08:24 pm
 KK-JP
 DRAWN:
 CHECKED:

 PROJECT NO:
 DRAWING NO:
 REVISION:


 1944
 A305
 1

Page 20 of 35 Building Consent BCO10375996 Approved by Auckland Council



DOORS & WINDOWS SCHEDULE - WEST

A306 1:50 @ A3



DOORS & WINDOWS SCHEDULE - SOUTH A306

1:50 @ A3

EXTERNAL GLAZING NOTE: 21/03/2024
ALL GLAZING TO COMPLY WITH F2/AS1 1.0

GLAZING AND NZS4223.3: 2016 PARTS 1-3. WINDOW OPENINGS TO COMPLY WITH F4/AS1 - CLAUSE 2.0 OPENING WINDOWS. (APPLY WHERE THE POSSIBLE HEIGHT OF FALL FROM OPENING WINDOW IS MORE THAN 1000MM. (THE HEIGHT OF FALL SHALL BE MEASURED FROM THE INSIDE FLOOR LEVEL ADJACENT TO THE WINDOW). ALLOW TO PROVIDE RESTRICTOR (R)

STAYS TO WINDOWS LESS THAN 1.0 WIDE WITH SILL HEIGHTS LESS THAN 760mm ABOVE FINISHED FLOOR LEVEL IN ACCEPTANCE WITH NZBC F2/AS1.

OPENING LESS THAN 1000MM WIDE SHALL HAVE; EITHER -

A) THE LOWER EDGE OF THE OPENING AT LEAST 760MM ABOVE FLOOR LEVEL, OR B) A RESTRICTOR FITTED TO LIMIT THE

MAX. OPENING SO THAT A 100MM DIAMETER SPHERE CANNOT PASS THROUGH IT.

OPENING GREATER THAN 1000MM WIDE SHALL HAVE -

A) THE LOWER EDGE OF THE OPENING AT A HEIGHT MIN. 1000MM ABOVE FLOOR

WINDOW MANUFACTURER SHALL CHECK ON SITE ALL WINDOW OPENING SIZES PRIOR TO ASSEMBLY. ALL GLAZING TO BE LOW-E DOUBLE GLAZED ALUMINIUM JOINERY 4mm GLASS /

12mm CAVITY / 4mm GLASS WITH AN SRI VALUE OF 56 OR OTHERWISE NOTED.

SAFETY GLASS NOTE:

SAFETY GLASS (SG) TO WINDOWS & SHOWERS LOCATED IN THE ENSUITE & BATHROOM& WINDOWS WITHIN 800MM OF



LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE


DOORS & WINDOWS SCHEDULE

A306


SCALE AT A3: DATE ISSUE:

1944

As indicated 4/03/2024 12:08:26 pm KK-JP



SECTION 1-1 A401 1:75@A3



SECTION 2-2 1:75@A3

TRS5 - 0.40BMT METAL LONG RUN ROOFING - INSTALL TO MANUFACTURER SPECIFICATIONS FOR SEA SPRAY ZONE

TIMBER TRUSSES
REFER TO TRUSS MANUFACTURER'S LAYOUT AND

RAFTERS

REFER TO STRUCTURAL DRAWINGS & **SPECIFICATIONS**

H1.2 70X45MM ON FLAT @900 CTRS MAX. 900MM CRS MAX (@ INTERMEDIATE SPAN) 600MM CRS MAX (@ END SPAN) FIXED WITH 1/14G TYPE 17 SELF DRILLING SCREW, 100MM LONG

CEILING BATTENS

SG8 H1.2 70X35MM TIMBER CEILING BATTENS AT 450 CTRS MAX FIXED WITH POWER DRIVEN NAILS OVER 10MM GIB LINING

EXTERNAL WALL

90X45MM SG8 H1.2 TIMBER FRAMING ON 20X40MM H3.1 DRAINED AND VENTED CAVITY BUILDING UNDERLAY AND INSULATION AS SPECIFIED 2.4M HT STUDS @600CRS MAX 2.7M HT STUDS @400CRS MAX

NOGGINGS

70S BRICK CLADDING @ 800CRS MAX LINEA OBLIQUE VERTICAL @ 600CRS MAX

90X45MM SG8 H1.2 TIMBER FRAMING AT 800 CRS MAX

LOAD BEARING WALL (LBW)

90X45MM SG8 H1.2 TIMBER FRAMING AT 400 CRS MAX BOTTOM PLATES SG8 H1.2 TIMBER FRAMING

INTERIOR LININGS

DRY AREAS WALL GIB STANDARD 10 MM CEILING GIB STANDARD 10 MM WET AREAS WALLS GIB AQUALINE 10 MM **CEILING GIB AQUALINE 10 MM**

THERMAL INSULATION

CEILING PINK BATTS ROOF INSULATION R 7.0 PINK BATTS WALL INSULATION R 2.0 GLAZING ALUMINIUM JOINERY TO BE LOW-E DOUBLE GLAZED R0.46

FLOOR KOOLFOAM ECO PODS R5.3

WATERPROOFING MEMBRANE ARDEX WPM SYSTEM INSTALLED TO MANUFACTURER'S SPECIFICATION

THERMAKRAFT COVERTEK 407 MARSHALL TEKTON SUPERCOURSE 500™ THERMAKRAFT THERMATHENE ORANGE™ 300

CONCRETE FOUNDATION

FOUNDATION TO ENGINEER'S DESIGN

TIMBER GRADES

TIMBER AND STEEL

ALL TIMBER TO BE TREATED AND GRADED AS FOLLOWS UNLESS OTHERWISE NOTED ON DRAWINGS: TOP PLATE: SG8 GRADE, H1.2 TREATED SG8 GRADE, H1.2 TREATED LINTEL: SG8 GRADE, H1.2 TREATED BOTTOM PLATE: SG8 GRADE, H1.2 TREATED TOP PLATE TO STUD FIXING 2/90 X 3.15 END NAILS + 2 WIRE DOGS TOP/ BOTTOM PLATES TOP & BOTTOM PLATES TO BE SG8 90 X 45 ALLOW DPC BETWEEN TIMBER AND CONCRETE;

21MR/20194

- EXTERIOR SG8 H1.2 TIMBER FRAMING, STUDS @400 CTRS,NOGGS @600CRS MAX
- EXTERIOR SG8 H1.2 TIMBER FRAMING, STUDS @400 CTRS, NOGGS @800CRS MAX
- INTERIOR 90 MM X 45 MM TIMBER FRAMING, STUDS @600 CTRS AND NOGGS @800 CTRS,
- TF4 LBW 90X45MM SG8 H1.2 TIMBER STUDS @400 CTRS MAX, 10MM THK GIB BOTH SIDES
- TIMBER TRUSSES SG8 H1.2 @ 900 CRS. MAX, REFER TO TRUSS **DESIGN DOCUMENTS**
- TIMBER RAFTER SG8 H1.2 @ 900 CRS. MAX., REFER TO STRUCTURAL **ENGINEERS DRAWING**
- 12 R7.0 CEILING INSULATION
- 13 R5.3 PODS INSULATION

EXTERIOR FINISH LEGENDS:



LINEA OBLIQUE VERTICAL (300MM) CLADDING ON 20MM CAVITY



70S BRICK CLADDING ON 50MM CAVITY



TRS 5, 0.55 BMT METAL LONG RUN ROOFING **OVER PURLINS**

| STATUS: | BUILDING COI | NSENT |
|---------|------------------|------------|
| REV | DESCRIPTION | DATE |
| 1 CHAN | IGE: FFL UPDATED | 25/01/2024 |

Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand

PH: 09 265 19 55 www.siliconarchitecture.com admin@siliconec.co.nz

© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted

STONEX HOMES


PROJECT

PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

PROPOSED SECTIONS SCALE AT A3: DATE ISSUE:

As indicated 4/03/2024 12:08:27 pm KK-JP EVISION: A401 1 1944




Page 23 of 35 Building Consent BCO10375996 Approved by Auckland Counter the 30 x 3.15MM -0.55BMT COLORSTEEL ENDURA METAL -LUMBERLOK CT200 BOTH SIDES FLASHING FIXED WITH PRE-FINISHED SELF DRILLING/TAPPING SCREW WITH FULLY NAILED WITH 30 X 3.15MM PLUS 2/90MM SKEW RUBBER WASHER AND WAFER TEK DRIVEN NAILS SCREW ON SIDE AT LEAST 2 CREST H1.2 SG8 90X45 OUTRIGGER SPACE @ 700CRS WITH 70X45 PURLIN ON TOP FIX WITH 90MM NAILS @ 50MM CRS. LUMBERLOK JOIST HANGER JH47X90 FULLY NAILED WITH 30 X 3.15MM 140X45 FLY RAFTER -6MMTHK SOFFIT LINING REFER TO TRUSS DOCUMENTS H3.2 TIMBER SCOTIA BEAD 0.40BMT COLORSTEEL ENDURA, METAL SG8 H3.2 GABLE END LONG RUN ROOF FIXED WITH PRE-**FRAMING** FINISHED SELF DRILLING/TAPPING SCREW WITH RUBBER WASHER OVER -WALL UNDERLAY 70X45MM PURLINS AT 900 CTRS, WITH ROOF UNDERLAY 20MM CAVITY BATTEN, FIXED WITH 40 X -SG8 H1.2 TIMBER TRUSSES @ 900 CRS. 2.8MM OR LONGER HARDIEFLEX™ NAIL. MAX FIXED TO MANUFACTURER'S SPECIFICATIONS LINEA OBLIQUE (VERTICAL) CLADDING FIXED 0.55BMT COLORSTEEL ENDURA 125 WITH 75 X 3.06MM 'D' HEAD NAIL OR 75 X 3.15 -EAVE FLASHING FIXED WITH SS ROUNDRIVE NAIL (HOT DIPPED GALVANISED FLAT HEAD NAIL OR RING SHANK STAINLESS STEEL) CONT. BLOCKING SUPPORT TAYLOR SPOUTING SYSTEM GUTTER WITH **GUTTER STRAP FIXED OVER H3.2 TIMBER** FASCIA WITH 8G WAFER-TEK SCREWS. TO VERGE OUTRIGGER DETAIL - VERTICAL CLADDING MANUFACTURERS SPECIFICATION A202 1:10@A3 H3.2 TIMBER FASCIA BOARD 190X25MM -6MMTHK SOFFIT LINING -H3.2 TIMBER SCOTIA BEAD -0.55BMT COLORSTEEL ENDURA, METAL LONG



-20MM CAVITY BATTEN, FIXED WITH 40 X 2.8MM OR LONGER HARDIEFLEX™ NAIL.

1 EAVE-SOFFIT DETAIL - VERTICAL CLADDING
A202 1:10 @ A3







DETAIL - ROOF JUNCTIONS

4/03/2024 12:08:31 pm JP-J


A501


JS

SCALE AT AS

PROJECT NO


1944






A202

1:10 @ A3



DESCRIPTION

1:10@A3




BCO103759961Received by Auckland Council 07/03/2024

1944

A503

A202

1:10 @ A3





DESCRIPTION

BUILDING CONSENT

Architecture Limited

Bldg. 8 level 1, 15 Accent Drive East Tamaki

Auckland, New Zealand

PH: 09 265 19 55

© Copyright 2021. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon

Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited.

The information contain in this set of drawings are to

use of contractor & LTA only. Any type of

reproduction is not permitted

STONEX HOMES

PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

DETAIL - EXTERNAL WALL CORNER

4/03/2024 12:08:36 pm JP-J


A505

JS

PROJECT

SCALE AT AS


ROJECT NO 1944



WALL VERTICAL JUNCTION - PLAN (BRICKXOBLIQUE) A205 1:5@A3


LINEA OBLIQUE (VERTICAL) CLADDING FIXED WITH 75 X 3.06MM 'D' HEAD NAIL OR 75 X 3.15 SG8 H1.2 TIMBER FRAMING ROUNDRIVE NAIL (HOT DIPPED GALVANISED WITH R2.4 WALL INSULATION OR RING SHANK STAINLESS STEEL) -10 mm GIB lining 20MM CAVITY BATTEN, FIXED WITH 40 X 2.8MM OR LONGER HARDIEFLEX™ NAIL. CONT.WALL UNDERLAY TO CORNERS-H3.2 45X20MM VERTICAL TIMBER CAVITY BATTENS, FIXED WITH-20 40-50MM SS CLOUT @300CRS LINEA OBLIQUE ALUMINUM EXTERNAL BOX CORNER

EXTERNAL CORNER - VERTICAL OBLIQUE A205 1:5@A3



SG8 H1.2 Timber framing with R2.4 wall insulation 70mm Series brick cladding -10 mm GIB lining on 50mm cavity S/S brick ties screw fixed to timber framing; spacing within 1st row @ 400mm of the rebate or 2 courses (whichever is smaller) Cont.wall underlay to corners

EXTERNAL CORNER - BRICK A205 1:5@A3





A305

1:5@A3

WALL BASE SECT - OBLIQUE VERTICAL A401 1:5@A3

Cavity base closure positioned to give 15mm drip edge to cladding

SG8 H1.2 Timber framing wall with S/S brick ties screw fixed to timber R2.4 wall insulation framing; spacing within 1st row @ -10 mm GIB wall lining 400mm of the rebate or 2 courses (whichever is smaller) -H3.2 timber bottom plate fixed with Screw bolt @ 600crs, min. 70mm Series brick cladding embedment 90mm on 50mm cavity -DPC separation to timber and Wall underlay -H3.1 timber skirting board Mortared slope with minimum 2 coats Selected floor finish of flintcote Weephole/vents in perpend @800mm Fosroc mulseal DP, applied to both faces exposed foundation/slab Concrete foundation, refer to structural drawing

Concrete foundation, refer to structural drawing

WALL BASE DETAIL - SECT (70S BRICK) A401

1:5@A3

DOOR BASE DETAIL - SECTION (BRICK)

LUMBERLOK JOIST HANGER JH47X90 FULLY NAILED WITH 30 X 3.15MM 0.55BMT COLORSTEEL ENDURA METAL FLASHING FIXED WITH PRE-FINISHED -LUMBERLOK CT200 BOTH SIDES FULLY NAILED WITH 30 X SELF DRILLING/TAPPING SCREW WITH 3.15MM PLUS 2/90MM SKEW RUBBER WASHER AND WAFER TEK DRIVEN NAILS SCREW ON SIDE AT LEAST 2 CREST

Concrete foundation, refer to structural drawing

> H1.2 SG8 90X45 OUTRIGGER SPACE @ 700CRS WITH 70X45 PURLIN ON TOP FIX WITH 90MM NAILS @ 50MM CRS. LUMBERLOK JOIST HANGER JH47X90 FULLY NAILED WITH 30 X 3.15MM 140X45 FLY RAFTER

6MMTHK SOFFIT LINING

125 SQ POST S/S BRICK TIES SCREW FIXED TO TIMBER FRAMING; SPACING WITHIN 1ST ROW @400MM OF THE REBATE OR 2 COURSES (WHICHEVER IS SMALLER) 70MM SERIES BRICK CLADDING ON 50MM CAVITY MORTARED SLOPE WITH MINIMUM 2 COATS OF FLINTCOTE WEEPHOLE/VENTS IN PERPEND @ 800MM CRS MAX FOSROC MULSEAL DP, APPLIED TO BOTH FACES EXPOSED FOUNDATION/SLAB

COLUMN BASE DETAIL - SECT (70S BRICK) 125SQ

21/03/2024





with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted

STONEX HOMES

PROJECT

PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE


DETAIL - WALL BASE JUNCTIONS SCALE AT A3 ATE ISSUE: DRAWN: 4/03/2024 12:08:37 pm JP-J

ROJECT NO A506

JS







Outline of turn up flashing tape beyond at 100mm min. at trimmer -Timber packer Selected double glazed window in powder -DPC separation to timber and coated aluminium concrete 4.5 - 7mm SIKAFlex at Facade sealant over pef rod over Marshall Superstick flashing tape WANZ support angle to H3.1 timber skirting board be supplied by window manufacturer SIKAflex MS sealant between cladding and joinery Concrete foundation, refer to structural drawing

DOOR BASE DETAIL - SECTION

GARAGE DOOR HEAD & SILL - SECTION (BRICK CLADDING) A305 1:5@A3 S/S BRICK TIES SCREW FIXED TO TIMBER FRAMING; SPACING WITHIN 1ST ROW @ 400MM OF THE REBATE OR 2 COURSES (WHICHEVER IS SMALLER) GALVANISED METAL OR 200MM 70MM SERIES BRICK SUPERCOURSE 500 POLYTHENE FLASHING-TAKEN 200MM PAST OPENING

CLADDING ON 50MM CAVITY 1-2MM GAP WITH 15MM COVER TO H3.2 20X20 KICK OUT BATTEN-LINE OF HEAD FLASHING -ABOVE WALL UNDERLAY DRESSED INTO THE FRAMED OPENING WITH MARSHALL SUPERSTICK FLEXIBLE FLASHING TAPE OVERAT CORNERS TIMBER PACKER 4.5 - 7MM SIKAFLEX MS SEALANT OVER PEF ROD OVER MARSHALL SUPERSTICK

bevond at 100mm min. at trimmer Selected double glazed window studs in powder coated aluminium Timber packer -DPC separation to timber and concrete WANZ support angle to 4.5 - 7mm SIKAFlex at Facade be supplied by window sealant over pef rod over Marshall manufacturer Superstick flashing tape SIKAflex MS sealant -H3.1 timber skirting board between cladding and-Concrete foundation, refer to structural drawing

Outline of turn up flashing tape

STONEX HOMES PROJECT PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

DESCRIPTION

BUILDING CONSENT

Architecture Limited

Bldg. 8 level 1, 15 Accent Drive East Tamaki

Auckland, New Zealand

PH: 09 265 19 55

© Copyright 2021. This design shall remain copyright with Silicon Architecture Limited.

This drawing remains the property of Silicon

Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted

DETAIL - GARAGE JOINERY / WALL PENETRATION

SCALE AT AS 4/03/2024 12:08:40 pm JP-J PROJECT NO 1944 A508

FLASHING TAPE

10X40MM PQ TIMBER ARCHITRAVE

WINDOW BASE DETAIL - SECTION

GARAGE JAMB DETAIL - PLAN (BRICK CLADDING) A305

1:5@A3

21/03/2024



DESCRIPTION **BUILDING CONSENT** Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55 www.siliconarchitecture.com admin@siliconec.co.nz © Copyright 2023. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted

PROJECT PROPOSED RESIDENCE

STONEX HOMES

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

DETAIL - WALL PENETRATIONS

SCALE AT A3: DATE ISSUE: As indicated 4/03/2024 12:08:41 pm DESIGN: KK-JP 1944 A509


A509

1:5@A3

Page 32 of 35 Building Consent BCO10375996 Approved by Auckland Council

21/03/2024





Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55 www.siliconarchitecture.com admin@siliconec.co.nz © Copyright 2023. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted STONEX HOMES PROJECT PROPOSED RESIDENCE LOT 137, 8 GERTRUDE COLE ROAD

CLARKS BEACH, PUKEKOHE

DETAIL - OPENINGS

A510

4/03/2024 12:08:42 pm KK-JP

SCALE AT A3: DATE ISSUE

1944

PROJECT NO

DESCRIPTION

BUILDING CONSENT

TYPICAL LINTEL FIXING - PREVENT UPLIFT 1:10@A3

A510


TYP. GAS CYLINDER SET OUT 1:10@A3

are permitted in yellow shaded area

Page 33 of 35 Building Consent BCO10375996 Approved by Auckland Council Table 8.18 - Fixing of top plate of wall to supporting members such as studs and lintels at 600 mm

9kN TRUSS TO TOP PLATE FIXING

- ★ Complies with Table 10.15 NZS 3604:2011
- ★ Top mounted fixing allows additional face fixing if required



9KNTTP Code:

Material: CPC40 1.55mm G300 Z275 Galvanised Steel

Packed: 2 x CPC40 Cleats

4 x Type 17-14g x 35mm Hex Head Galvanised Screws 4 x Type 17-14g x 75mm Hex Head Galvanised Screws

FIXING TYPE B 4.7kN


CHOOSE ANY OF THE 3 OPTIONS BELOW

2 x 90mm x 3.15 dia. plain steel wire nails driven vertically into stud.





2 x 90mm x 3.15 dia. plain steel wire nails driven vertically into stud.



2 x LUMBERLOK CPC40

Recommended for internal wall options to avoid lining issues

2 x 90mm x 3.15 dia. plain steel wire nails driven vertically into stud.



centres (see 8.7.6 and figure 8.12)

| | 1 | | | Light | roof | | | | | | He | avy ro | of | | |
|--------------------------|--------------------------|---------|--------|---------|--------|---------|--------|--|--------------------|-----|-----------|--------|----------|-------------------|-----|
| | Roof member spacing (mm) | | - Ink | | | | | | | | | | | | |
| Loaded | | | 900 | BA | | | | 1200 | | 50 | 201 | | 900 | | 10 |
| dimension of wall (m) | | W | ind zo | ne | | | W | ind zo | ne | | Wind zone | | | EH B B B | |
| | L | М | н | VH | EH | L | М | Н | VH | EH | L | М | н | VH | EH |
| W. F. | 1 | TO F | | | | Fix | ing ty | pe (se | e belo | ow) | | F | | | 1 |
| 2.0 | А | A | В | В | В | A | A | В | В | В | А | A | A | В | В |
| 3.0 | А | В | В | В | В | А | В | В | В | В | Α | Α | В | В | В |
| 4.0 | Α | В | В | В | В | A | В | В | В | В | Α | А | В | В | В |
| 5.0 | В | В | В | В | В | В | В | В | В | В | Α | A | В | В | В |
| 6.0 | В | В | В | В | В | В | В | В | В | В | A | A | В | В | В |
| Fixing type | | | 7 | Fixir | g to r | esist ı | uplift | A STATE OF THE PARTY OF THE PAR | THE REAL PROPERTY. | | Ca | pacity | y of alt | | ive |
| A | 2/9 | 0 x 3.1 | 5 end | nails | | | | | | | | - | 0.7 | | |
| В | 2/9 | 0 x 3.1 | 5 end | nails + | 2 wire | dogs | | | 12 | | | | 4.7 | | |

SECTION 8 - WALLS


Table 8.19 - Nailing schedule for hand-driven and power-driven nails (see 8.8.6)

| | Hand-dr | iven nails | Power-driven nails | | | |
|---|--|--|--|--|--|--|
| Joint | Length (mm) x diameter (mm) and type | Number/ Location | Length (mm) x diameter (mm) and type | Number/ Location | | |
| Bottom plate to floor framing at: (a) External walls and internal wall bracing elements | 100 x 3.75 | 2 at 600 mm centres | 90 x 3.15 | 3 at 600 mm centres | | |
| (b) Internal walls (may be nailed to floor decking) (c) Trimmer not exceeding | 100 x 3.75 100 x 3.75 | 1 at 600 mm centres 4 (end nailed) | 90 x 3.15 90 x 3.15 | 1 at 600 mm centres 6 (end nailed) | | |
| 4.2 m long Dwang to stud | 75 x 3.15 or 100 x 3.75 | 2 (skewed) 2 (end nailed) | 75 x 3.06 90 x 3.15 | 2 (skewed) 2 (end nailed) | | |
| Fishplate to straightened stud | 60 x 2.8 | 4 each side of cut | 60 x 2.8 | 4 (each side of cut) | | |
| Half joint in top plate | 75 x 3.15 | 3 | 75 x 3.06 | 4 | | |
| Lintel to trimming stud | 75 x 3.15 or 100 x 3.75 | 4 (skewed) 2 (end nailed) | 90 x 3.15 | 3 (end nailed) | | |
| Ribbon board to stud | 100 x 3.75 | 2 | 90 x 3.15 | 3 | | |
| Sill or header trimmer to trimming stud for: (a) Trimmer not exceeding 2.4 m long (b) Trimmer not exceeding 3.0 m long (c) Trimmers not exceeding 3.6 m long | 100 x 3.75 100 x 3.75 100 x 3.75 | 2 (end nailed) 3 (end nailed) 4 (end nailed) | 90 x 3.15 90 x 3.15 90 x 3.15 | 3 (end nailed) 5 (end nailed) 6 (end nailed) | | |
| Solid plaster batten to stud | 60 x 2.8 (galv.) | 500 mm centres | 60 x 2.8 (galv.) | 500 mm centres | | |
| Stud to plate | 75 x 3.15 or 100 x 3.75 | 4 (skewed) 2 (end nailed) | 75 x 3.06 90 x 3.15 | 4 (skewed) 3 (end nailed) | | |
| Top plate 140 mm x 35 mm to 90 mm x 45 mm and top plate to lintel | 100 x 3.75 | 2 at 500 mm centres | 90 x 3.15 | 3 at 500 mm centres | | |
| Trimming studs at openings, blocking and studs at wall intersections | 100 x 3.75 | 600 mm centres | 90 x 3.15 | 600 mm centres | | |
| Trimming stud to doubled stud immediately under lintel | 100 x 3.75 | 2 | 90 x 3.15 | 2 | | |
| Waling to stud | 60 x 2.8 | 2 | 60 x 2.8 | 2 | | |

M10 X 140 BOWMAC BLUE HEAD

- ★ Complies with Clause 7.5.12.2 NZS 3604:2011 Proprietary Post Fixed Anchors
- * BRANZ tested. Ref# ST0895 Oct. 2012
- * Suitable for both external and internal wall frame anchor to concrete slab or masonry header blocks
- Complies with durability requirements for "All Zones" in a "CLOSED" environment as defined in Table 4.1 NZS 3604:2011

See reverse side for installation details



Available from leading Builders Supply Merchants throughout New Zealand



NZS 3604:2011

DESCRIPTION **BUILDING CONSENT** Bldg. 8 Level 1, 15 Accent Drive East

Tamaki Auckland, New Zealand PH: 09 265 19 55 www.siliconarchitecture.com admin@siliconec.co.nz

© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted

STONEX HOMES

PROJECT PROPOSED RESIDENCE


LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE


DETAIL - LUMBERLOK SCALE AT A3: DATE ISSUE: 4/03/2024 12:08:43 pm KK-JP PROJECT NO 1944 A511


BCO10375996 Received by Auckland Council 07/03/2024













E: BATH CRADLE LINING DETAIL



SHOWER - ACRYLIC LINER AND BASE DETAILS





D: SHOWER MIXER PENETRATION IN WET WALL LININGS


Refer to the shower mixer manufacturer for shower mixer installation detailing including the use of proprietary products to



B: CERAMIC FLOOR LINING JUNCTION










C: BATH LINING JUNCTION





G: SHOWER MIXER PENETRATION IN WET WALL LININGS

installation detailing including the use of proprietary products to prevent water or moisture ingress behind the wet wall lining.

Refer to the shower mixer manufacturer for shower mixer

GIB® HELPLINE 0800 100 442 OR GIB.CO.NZ FOR MORE INFO FEBRUARY 2021

GIB® WET AREA SYSTEMS

GIB® WET AREA SYSTEMS

GIB® HELPLINE 0800 100 442 OR GIB.CO.NZ FOR MORE INFO

FEBRUARY 2021

DESCRIPTION **BUILDING CONSENT** Bldg. 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55

© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited. This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited. The information contain in this set of drawings are to use of contractor & LTA only. Any type of

reproduction is not permitted

STONEX HOMES

www.siliconarchitecture.com admin@siliconec.co.nz

PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE **DETAIL - GIB WET AREAS** SCALE AT A3: DATE ISSUE:

4/03/2024 12:08:44 pm KK-JP

A512


PROJECT NO

1944







A: BENCH TOP LINING JUNCTION



CERAMIC FLOOR SKIRTING LINING JUNCTION



B: COOKTOP LINING JUNCTION



B. COOKTOF LIMING SONOTIO



GIB® HELPLINE 0800 100 442 OR GIB.CO.NZ FOR MORE INFO

GIB® WET AREA SYSTEMS

25

STATUS: BUILDING CONSENT

STATUS: BUILDING CONSENT

STATUS: BUILDING CONSENT

PROPRIES

ARCHITECTURE

Bldg. 8 Level 1, 15 Accent Drive East

ldg, 8 Level 1, 15 Accent Drive East Tamaki Auckland, New Zealand PH: 09 265 19 55 www.siliconarchitecture.com admin@siliconec.co.nz

© Copyright 2023. This design shall remain copyright with Silicon Architecture Limited.

This drawing remains the property of Silicon Architecture Limited & may not reproduce without the written permission of Silicon Architecture Limited.

The information contain in this set of drawings are to use of contractor & LTA only. Any type of reproduction is not permitted.

CLIENT:

STONEX HOMES

ROJECT:

PROPOSED RESIDENCE

LOT 137, 8 GERTRUDE COLE ROAD CLARKS BEACH, PUKEKOHE

DETAIL - GIB WET AREAS

SCALE AT A3: | DATE ISSUE: | DESIGN: | DRAWN: |

 SCALE AT A3:
 DATE ISSUE:
 DESIGN:
 DRAWN:
 CHECKED:

 1:5
 4/03/2024 12:08:46 pm
 KK-JP
 J
 CHECKED:

 PROJECT NO:
 DRAWING NO:
 REVISION:
 A513